

SAFETY DATA SHEET

Creation Date 10-Jan-2019 SECTION 1: Identification

Product Name: Identified Uses: Company Methyl Isobutyl Ketone Solvent EM Resist Ltd. Media House Adlington Business Park Macclesfield SK10 4NL UNITED KINGDOM +44 (0)1625 813723 info@emresist.com +44 (0)1625 813723

SECTION 2: Hazards identification

Classification

Telephone

E-mail Address

Emergency Phone #

Flammable liquids	(Category 2)
Acute toxicity, Inhalation	(Category 4)
Serious eye damage/eye irritation	(Category 2A)
Carcinogenicity	(Category 2)
Specific target organ toxicity	(Category 3) (respiratory system)

Label Elements

Pictogram



Signal Word

Danger

Hazard statement(s) :		Precautionary statement(s):	
H225	Highly Flammable liquid and vapour	P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
H319	Causes serious eye irritation	P261	Avoid breathing dust/fume/gas/mist/vapours/spray
H332	Harmful if inhaled	P280	Wear protective gloves/protective clothing

Revision Date 10-Feb-2023

- H335 May cause respiratory irritation
- H351 Suspected of causing cancer if inhaled

P303 +	IF ON SKIN (or hair): Remove/Take
P361+	off immediately all contaminated
P353	clothing. Rinse skin with
	water/shower.
P271	Use only outdoors or in a
	well-ventilated area.
P233	Keep container tightly closed
P240	Ground/bond container and
	receiving equipment
P241	Use explosion proof electrical,
	lighting, ventilation equipment
P242	Use only non-sparking tools
P243	Take precautionary measures
	against static discharge
P264	Wash exposed skin thoroughly
	after handling
P305 +	If in eyes: Rinse cautiously with
P351 +	water for several minutes. Remove
P338	contact lenses, if present and easy
	to do. Continue rinsing.
P312	Call a POISON CENTRE or
	doctor/physician if you feel unwell
P337 +	If eye irritation persists: Get
P313	medical advice/attention
P370 +	In case of fire: Use CO ₂ , dry
P378	chemical or foam for extinction.
P403	Store in a well-ventilated place.
	Keep container tightly closed

SECTION 3: Composition / information on ingredients

Component	Weight %
Methyl isobutyl ketone	100%
CAS: 108-10-1	

SECTION 4: First-aid measures	
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention if irritation persists.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if irritation persists.
Inhalation	Move to fresh air. If breathing is difficult give oxygen. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting. Give lots of water to drink. Obtain medical

attention

Most important	Breathing difficulties. Symptoms of overexposure may be
symptoms/effects	headaches, dizziness, tiredness, nausea and vomiting.

SECTION 5: Fire-fighting measures

Suitable Extinguishing Media	User water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray.
Flash Point	14°C / 57.2°F
Autoignition Temperature	460°C / 860°F
Specific Hazards Arising from the Chemical	Flammable. Risk of ignition. Vapours may from explosive mixtures with air. Vapours may travel to source of ignition and flash back. Thermal decomposition can lead to release of irritating gases and vapours. Keep product and empty container away from heat and sources of ignition.
Hazardous Combustion Products	No hazardous combustion products are known
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: Accidental release measures

Personal Precautions	Use personal protective equipment as required. Remove all sources of ignition. Ensure adequate ventilation. Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing
Environmental Precautions	Avoid release to the environment
Methods for Containment and Clean Up	Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion- proof equipment

SECTION 7: Handling and storage

Handling	Wear person protective equipment. Keep away from open
	flames, hot surfaces and sources of ignition. Ensure adequate
	ventilation. Use spark-proof tools and explosion-proof
	equipment. Take precautionary measures against static

discharge. Avoid contact with skin, eyes and clothing

StorageKeep containers tightly closed in a dry, cool and well ventilated
place. Keep away from heat and sources of ignition.
Flammables areas

SECTION 8: Exposure controls/personal protection

Exposure Guidelines:

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	ACGIH STEL
Methyl isobutyl	TWA: 20 ppm	TWA: 100 ppm	-	TWA: 75 ppm
ketone				

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice

SECTION 9: Physical and chemical properties

Physical State
Appearance
Odor
Odor Threshold
рН
Melting Point/Range
Boiling Point/Range
Flash Point

Liquid Colorless Alcoholic Ketone No Information available No Information available 117°C / 243°F @ 760 mmHg 14°C / 57°F

Evaporation Rate Flammability (solid,gas)	No information available Not applicable
Flammability or explosive limits	
Upper	8.0 vol %
Lower	1.2 vol %
Vapor Pressure	No Information available
Vapor Density	No Information available
Relative Density	0.80
Solubility	Moderate solubility in water
Autoignition Temperature	460°C / 860°F
Decomposition Temperature	No information available
Partition coefficient: n-	No information available
octanol/water	
Viscosity	No information available

SECTION 10: Stability and reactivity

Reactive Hazard	Vapours may form explosive mixture with air
Stability	Stable under normal conditions
Conditions to avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition
Incompatible Materials	Strong oxidising agents
Hazardous Decomposition Products	None known
Hazardous Polymerisation	Hazardous polymerisation does not occur
Hazardous Reactions	May form explosive peroxides

SECTION 11: Toxicological information

Acute Toxicity

Product Information Component Information

Common and			I CEO luck a lation
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl isobutyl	>2000 mg/kg (Rat)	>2000 mg/kg	>10 - 20 mg/L (Rat) 4h
ketone		(Rabbit)	

Toxicologically Synergistic	No information available
Products	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Irritating to eyes and skin
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any

ingredient as carcinogenic

Component IARC NTP ACGIH CAS No. **OSHA** Mexico Methylisobutyl 108-10-1 Group 2B Not listed A3 A3 х ketone **Mutagenic Effects** No information available **Reproductive Effects** No information available No information available **Developmental Effects** Teratogenicity No information available **STOT** – single exposure Central nervous system (CNS) STOT – repeated exposure Liver, Kidney Aspiration hazard No information available Symptoms/effects, both acute Symptoms of overexposure may be headache, dizziness, and delayed tiredness, nausea, and vomiting **Endocrine Disruptor** No information available Information

SECTION 12: Ecological Information

Ecotoxicity

Do not empty into drains

Component	Freshwater Algae	Freshwater fish	Microtox	Water Flea
Methyl	EC50: 400 mg/L/96h	LC50: 496 – 514 mg/L,	EC50 = 79.6	EC50: 4280.0
isobutyl		96h flow through	mg/L 5min	mg/L/24h
ketone		(Pimephales promelas)		EC50: 170 mg/L/48h
				EC50: 4280 mg/L/24h
BOD5 and CO) N	ot available		
Products of Biodegradation Possibly hazardous short term degradation products are not		products are not		
	li	kely. However, long term	degradation pro	oducts may arise.
Toxicity of the			С.	
Biodegradatio				
Special remark		ot available		
Products of Bi				

SECTION 13: Disposal Considerations

Product	Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to
	a licensed disposal company.
Contaminated Packaging	Dispose of as unused product.

SECTION 14: Transport Information

UN-No	UN1245
Proper Shipping Name	Methyl isobutyl ketone
Hazard Class	3
Packing Group	II

SECTION 15: Regulatory information

REACH Regulation (EC) No 1907/2006

This product contains only components that have been either pre-registered, registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH)., Polymers are exempted from registration under REACH. All relevant starting materials and additives have been either pre-registered, registered, or are exempt from registration to Regulation (EC) No. 1907/2006 (REACH)., The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

SECTION 16: Other information

Prepared By	EM Resist Ltd.
Creation Date	10-Jan-2019
Revision Date	10-Feb-2023
Revision Summary	This document has been updated to comply with the US OSHA
	HazCom 2012 Standard replacing the current legislation under
	29 CFR 1910.1200 to align with the Globally Harmonized System
	of Classification and Labeling of Chemicals (GHS)
	Updated contact details

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.